

lightbars

MX7000®

Two Level, Versatile Design



Benefits

- Patented dual-deck design provides rotator power on the upper deck and flexibility for special function lights on the lower deck
- Sweeping intersection light for maximum safety in high-risk situations
- Easy maintenance with field replaceable strobe components



Design Features

- LED, Strobe, Halogen or Combination
- 50W/55W Standard or Fast Rotators (Upper Level)
- 120° Sweeping Intersection Lights (Lower Level)
- All Light or Speaker Section
- Easy to Install LIT3 Mounting Platform

Options

- Build-Your-Own Base Models
- LED or Halogen ArrowStik®
- Lighted LIT3 Mounting Kit (LED and/or 55W Halogen)

Specifications

- 18" (457 mm), 36" (914 mm), 47" (1194 mm), 52" (1321 mm), 58" (1473 mm), 69" (1753 mm), 80" (2032 mm) and 91" (2311 mm) Lengths
- 12"W x 5.75"H (305 x 146 mm)
- 12 Volt (24 Volt Option)
- Meets all applicable SAE, NFPA, ECE 65 and California Title 13 specifications when properly configured.

Excalibur®

Halogen/Strobe/LED Lightbars



Range of features in a 4 1/2" tall lightbar

Benefits

- Select an LED, strobe, halogen or combination bar to suit your application



Design Features

- 50W/55W Standard or Fast Rotators (Upper Levels)
- High Gloss Strobe Reflectors
- Easy to Install LIT3 Mounting Platform

Options

- Build-Your-Own Base Models
- LED or Halogen ArrowStik®
- Lighted LIT3 Mounting Kit (LED and/or Halogen)
- Compact Cyclone Speaker fits in the 47" and 52" Excalibur. Meets SAE 1849.

Specifications

- 18" (457 mm), 22.5" (572 mm), 36" (914 mm), 47" (1194 mm), 52" (1321 mm), 58" (1473 mm), 69" (1753 mm), 80" (2032 mm) and 91" (2311 mm) Lengths
- 12.25"W x 4.5"H (311 x 114 mm)
- 12 Volt (24 Volt Option)
- Meets all applicable SAE, NFPA, ECE65 and California Title 13 specifications when properly configured.