

DuoBeam™ II

CODE 3[®]
A PUBLIC SAFETY EQUIPMENT COMPANY
www.code3pse.com

NFPA DuoBeam II Available in 3 LED Technologies!

DB2-2TCNFPA2



TriCore® Model: Code 3's World Class TriCore (6) Lighthoods are available in Red, Amber, and Blue LEDs with matching or Clear lens. White LEDs with clear lens only. Red/Red and Red/Clear are NFPA compliant.

DB2-2LMCNFPA1



PriZm™ II MultiColor Model: PriZm II (12) are available in MultiColor (Red, Blue, Amber, White)—Red/Blue and Red/Amber LEDs with Clear Lens are NFPA compliant. Flashes one color then the other.

DB2-2PZNFPA1



PriZm™ II Solid Color Model: PriZm II (12) are available in Solid Colors: Red, Blue, Amber, and White with matching or Clear lens. White LEDs with clear lens only. Red Lens/Red LEDs and Red Lens/Clear LEDs are NFPA compliant.

DB2-2TSSNFPA2



Torus™ Double Stack Model: Torus (6) LEDs are double stacked in Red, Amber, and Blue with matching or Clear lens. White LEDs with Clear lens only. Separate colors on top & bottom available: Red/Blue, Red/Amber and Blue/Amber are NFPA compliant with Clear Lens.*

Benefits

- ▶ Choose from one of three different LED technologies and a variety of options designed to meet your needs and your budget!
- ▶ New streamlined square shape is designed to output a large amount of light—great in pairs for each side of the apparatus.

Features

- NFPA Models Priced in Pairs
- Durable and Moisture Resistant
- Available in Single Stack TriCore, PriZm II, and Torus LED Lighthoods. Torus Lighthoods Also Available in Double Stack.
- PriZm II LED Lighthoods also Available in MultiColor
- Matching Colored Lens & LEDs or Clear Lens with Red, Blue, Amber, or White LEDs
- Standard Lightbar Mounting (Carriage Bolt Track)
- Mounting Kits Available – Flush Mount, Magnetic Mount, Mirror Mount, and Pylon Mount
- Independent Flashing Heads or CC Heads Available
- Multiple Flash Patterns include NFPA Approved Patterns

Specifications

- 15' cable & 35' cable
- 10.3" L x 10.3" W x 3.3" H (262 mm x 262 mm x 84 mm)
- Carriage bolt track spacing – 3.25"
- 6 lbs
- 12 Volt
- 0.5 Amps avg per Torus Module (double stack), 0.6 Amps avg per PriZm II Module for 8 LEDs, 0.8 Amps avg per PriZm II Module for 12 LEDs, 1.2 Amps avg per TriCore Module
- 5-Year Warranty on LEDs
- Meets SAE J845, NFPA and California Title 13 requirements when properly configured.
- * Single Stack Torus (6) is NFPA Compliant for Red LEDs only.

