



# Metafix

## PRODUCT INFORMATION BULLETIN

### ARU Electrolytic Silver Recovery Series

The Metafix ARU series of electrolytic silver recovery systems are designed to meet the environmental needs of NDT, medical x-ray, graphic arts and black and white photo facilities.

Featuring state of the art digital microprocessor controls, digital display and keypad for easy calibration and information storage.

These models automatically control and optimise plating current as the silver concentration varies in the fixer solution.



	ARU-700	ARU-1200	ARU-2100
Capacity	23 g/hour	46 g/hour	92 g/hour
Typical Application	7.5 L/8 hrs	15 L/8 hrs	30 L/8 hrs
Dimensions	15W/15D/21H	15W/15D/21H	15W/15/D/27.5H (inches)
Shipping Weight	20.4Kg	21.3Kg	26.3Kg
Electrical	115/230VAC	115/230VAC	115/230VAC
Power Requirements	50/60Hz 20W	50/60Hz 50W	50/60Hz 100W
Inlet/Outlet Tubing	1/4"	1/4"	1/4"

### Features and Benefits

- ◆ Capable of servicing one or two processors
- ◆ Secondary treatment can be easily added
- ◆ Digital microprocessor calculates plating activity from the last cathode desilvering
- ◆ Automatically switch to standby mode when silver level is reduced to optimum level. Prevents sulphiding
- ◆ Flashing "error" message appears if the unit is not plating silver
- ◆ Easy to desilver and maintain

### Metafix (UK) Limited

1 Dean Close  
Raunds  
Wellingborough  
Northamptonshire  
NN9 6BD England

Tel: +44 (0)1933 461907  
Fax: +44 (0)1933 461484  
E-mail: sales@metafix.co.uk  
www.metafix.co.uk