

# HEAVY DUTY AIR NIPPER

THESE AIR NIPPERS ARE IDEAL AND WIDELY FOR CUTTING JOBS IN MASS PRODUCTION FACTORIES



YM-40 NIPPER



YM-60 NIPPER

מפעלים  
מטבחיים  
מפעלי  
התעשייה  
0770 06-242265  
06-242265

## REMARKS:

- OIL PIVOT 2 OR 3 TIMES DAILY
- BLANK ACTION MAY RUIN CUTTERS
- USE RECOMMENDED AIR PRESSURE



S2 BLADE  
( 005 NIPPER FIT )



S4 BLADE  
( 670 NIPPER FIT )

MODEL	LENGTH MM	GRIP SIZE MM $\phi$	WEIGHT G	AIR CONSUMPTION CM $^3$ /STROKE	POWER KG/cm $^2$	AIR PRESSURE KG/cm $^2$	BLADE	CUTTING CAPACITY MM $\phi$
YM-40	103	30	130	64	40	5.5	S2	1.0 0.5
YM-60	124	35	200	116	60	5.5	S4	1.6 1.0 4.0

## IMPORTANT:

- \*AIR PRESSURE(SKG/cm $^2$  (78 PSI) AIR PRESSURE IS RECOMMENDED FOR THE MOST EFFICIENT PERFORMANCE
- \*CLEAN AIR: DRAIN DAILY AND INSTALL FILTER AT OR NEAR THE TAKE-OFF POINT TO PREVENT FOREIGN MATTER
- \*PIVOT SHOULD BE OILED 2 TO 3 TIMES A DAY.
- \*NEVER ATTEMPT TO CUT WITHOUT WORK PIECE YOU WILL PROBABLY RUIN CUTTERS THROUGH SUCH ACTION.
- \*005, 010 CAN NOT CUT PLANO WIRE OR HARD STEEL WIRE IRRESPECTIVE OF DIAMETER.
- \*USE AIR NIPPER AND AIR SHEAR WITH THE SPECIFIED AIR PRESSURE(AIR SHOULD BE FREE FROM MOISTURE).
- \*ADJUST THE POSITION OF LEVER (PART NO.6) BY TURNING FEAR BODY (PART NO.2) ACCORDING TO THE JOE TO BE DONE. (NEVER TURN FEAR BODY MORE THAN 360 DEGREES)