

**ASTM D 2624 - ISO 6297 - IP 274**

**SCOPE**

Standard Test Methods for Electrical Conductivity of Aviation and Distillate Fuels.

**ELECTRICAL CONDUCTIVITY OF AVIATION AND DISTILLATE FUELS  
- CONDUCTIVITY METER MLA 900 -  
- REF 23628 -**

**MAIN CHARACTERISTICS**

- ✓ Portable conductivity meter
- ✓ Fully transistorized instrument
- ✓ Measuring range: 0 to 500 c.u. and 0 to 1000 c.u.
- ✓ Temperature measuring range : -20 to 60°C.

**SCOPE OF DELIVERY**

**CONDUCTIVITY METER delivered ready to use**

**OPTIONNAL ADDITIONAL BATTERY**

**REF 23629** Carbon/zinc spare battery, 9 V

**MEASURING THE CONDUCTIVITY OF AVIATION FUELS**

Conductivity and temperature can both be measured simultaneously in a liquid. The values are immediately shown on the large display. The instrument is compact, portable and approved for use in explosion-hazardous areas. The MLA900 provides a determination of the actual conductivity anytime and anywhere, quickly and safety.

**APPLICATIONS**

The MLA900 is suitable for conductivity measurement of aviation fuel, light oil products and other industrial liquids which can be electrostatically charged.



**ORDERING INFORMATION**

**REF 23628**

400 x 210 x 150 mm (± 5 kg).

CONTACT : [sales@normalab.com](mailto:sales@normalab.com)

NORMALAB FRANCE SAS  
ZA Caux Multipôles 1 - F-76 190 Valliquerville  
Tel. : +33 232 700 100  
Fax : +33 232 704 732

[www.normalab.com](http://www.normalab.com)

REF 23628 Leaflet 15

DISTRIBUTED BY