

**ASTM D 445 - ISO 3104 - IP 71 - DIN 51366****SCOPE**

Standard Test Method for Kinematic Viscosity of Transparent and Opaque Liquids and Calculation of Dynamic Viscosity

**SIMPLIFIED VISCOSITY BATH**  
**-REF 23831-**  
**-REF 23832-****MAIN CHARACTERISTICS****200°C maximum for reference 23832**

Constant temperature viscosity bath "Routine" (**max. 200°C**), same as above with glass jar of **20 liters**, digital temperature control and 5 places for common viscometers (suspension device not included)  
For use on AC 230V, 50Hz, 10A - 320x580x500mm (±17 kg)

**SCOPE OF DELIVERY**

The unit includes:

- Heating element with digital temperature readout
- 20 litres glass jar
- Five holes with covers

***Viscometer supports are not included (to be chosen according to the type of tubes)***

**NECESSARY ACCESSORIES**

- REF 10567** Stainles steel suspension for Ubbelohde viscometer  
**REF 10568** Nylon suspension for Cannon-Fenske viscometer  
**REF 10569** Nylon suspension for Ubbelohde viscometer

**OPTIONAL ACCESSORIES**

- REF 13539** Support for 6 viscometer tubes  
**REF 16419** Bottle of 5 liters of silicone oil up to 150°C  
**REF 16427** Bottle of 5 liters of mineral oil max. 100°C  
**REF 21375** Electronic stopwatch  
**REF 10025** ASTM Thermometer 120C, +38.5 to +41.5°C/0.05°C  
**REF 10026** ASTM Thermometer 121C, +98.5 to +101.5°C/0.05°C

**ORDERING INFORMATION****REF 23832**

For use on AC 230V, 50Hz, 1600w -

320x580x360mm (±17 kg)

CONTACT : [sales@normalab.com](mailto:sales@normalab.com)

NORMALAB FRANCE SAS  
14 rue des Lilas - F-76 210 Lintot  
Tel. : +332 35 38 59 59  
Fax : +332 35 38 78 55

[www.normalab.com](http://www.normalab.com)

SIMPLIFIED VISCOSITY BATH Brochure 14

DISTRIBUTED BY