

**ASTM D 113 - NFT 66006 & DIN 52013**

**SCOPE**

Standard Test Method for Ductility of Bituminous Materials.

**DUCTILITY OF BITUMINOUS MATERIALS**  
**- DM 150 CLASSIC -**  
**-REF 9418642-**

**MAIN CHARACTERISTICS**

- ✓ Ductility machine 3 posts
- ✓ Length 150 cm, with a circulation bath and thermostating coil
- ✓ Variable speed from 1 to 99 mm / min in steps of 0.1 mm,
- ✓ Background consisting of two plates of opaline reflective effect
- ✓ Draincock
- ✓ Drive motor with worm screw,
- ✓ Mobile assembly built in bearing
- ✓ Digital measurement display

**SCOPE OF DELIVERY**

DM 150 CLASSIC delivered ready for use with :

- REF 941868** Mould without brass plate  
**REF 941869** Brass plate  
**REF 941865** Opal glass for ductility meter 150 cm  
**REF 11532** ASTM thermometer (63C)

**ACCESSORIES**

- REF 22239** Cooling cryostat (-28/+100°C ±0.02)  
**REF 9418671** Transparent cover for ductility meter (1m50)



**ORDERING INFORMATION**

**REF 9418642**  
DM 150 CLASSIC For use on AC 230 V - 50 Hz - 3 A

(W) 2200x (D) 330x (H) 310 mm (± 85 kg)

CONTACT : [sales@normalab.com](mailto:sales@normalab.com)

NORMALAB FRANCE SAS  
ZA Caux Multipôles 1 - F-76 190 Valliquerville  
Tel. : +33 232 700 100  
Fax : +33 232 704 732

[www.normalab.com](http://www.normalab.com)

REF 9418642 Leaflet 15

DISTRIBUTED BY